

# HV RACK® CONFIGURABLE SERIES

## Rack Mount High Voltage Power System

The HV Rack Configurable power system is a fully featured, configurable chassis, enabling end users to select and to specify the UltraVolt high-voltage power supply (HVPS) operating in each channel from UltraVolt's catalog of more than 600 models. This combination provides accurate control and measurement of high-voltage power supply and HV system performance.

- 1 to 4 configurable high-voltage output channels
- Voltage ranges from 0 to 62VDC through 40kV
- 4 to 1000 watts per channel, up to 1000 watts total
- Independent control & monitoring of each channel



- Voltage and Current meters for each channel
- Constant current / Constant voltage auto-crossover
- Pre-set before & during bias capability
- PLC Analog/Digital Remote operation capability

| PARAMETER          | CONDITIONS                         | MODELS   |                     |                 |                 |  |  |  |
|--------------------|------------------------------------|--|---------------------|-----------------|-----------------|--|--|--|
| AC INPUT           |                                    | HV RACK X-250  | HV RACK X-500       | HV RACK X-750   | HV RACK X-1000  |  |  |  |
| Voltage            | Full Power, Autoswitching          | 115/230VAC, 50/60Hz  | 115/230VAC, 50/60Hz | 230VAC, 50/60Hz | 230VAC, 50/60Hz |  |  |  |
| Power              | 120VAC, Max Eout , Full Load       | 375W   | 750W                | N/A             | N/A             |  |  |  |
| Power              | 240VAC, Max Eout , Full Load       | 375W   | 750W                | 1125W           | 1500W           |  |  |  |
| REMOTE CONTROL     |                                    | ALL MODELS   |                     |                 |                 |  |  |  |
| Enable             | All Channels                       | TTL high to enable, low to disable (DEFAULT IS DISABLE)                              |                     |                 |                 |  |  |  |
| V Control          | All Channels                       | 0V to 4.64V = 0V to 100% HV out (5V = 108% HV out)                                   |                     |                 |                 |  |  |  |
| HV Monitor         | All Channels                       | 0V to 4.64V = 0V out to 100% V out (5V = 108% V out)                                 |                     |                 |                 |  |  |  |
| I Control          | All Channels                       | 0V to 4.64V = 0A to 100% Io (5V = 108% Io)   |                     |                 |                 |  |  |  |
| I Monitor          | All Channels                       | 0V to 4.64V = 0A to 100% Io (5V = 108% Io)   |                     |                 |                 |  |  |  |
| Reference Out      | All Channels                       | 5V precision voltage reference returned to signal ground                             |                     |                 |                 |  |  |  |
| LPVS Out           | One Signal, PTC Fused              | +15V±10%, 0 to 100mA   |                     |                 |                 |  |  |  |
| Power Ground       | One Signal                         | Return of LPVS Out   |                     |                 |                 |  |  |  |
| Global Disable     | One Signal                         | TTL signal disables all Channels, low to enable, high to disable (DEFAULT IS ENABLE) |                     |                 |                 |  |  |  |
| OUTPUT METERS      |                                    | TYPE OF CHANNEL  | TOLERANCE           |                 |                 |  |  |  |
| Voltage            | 4½ Digit Red LED                   | All  | 1% Full Scale       |                 |                 |  |  |  |
| Current            | 3½ Digit Blue LED                  | All  | 1% Full Scale       |                 |                 |  |  |  |
| TEMPERATURE        |                                    | ALL MODELS   |                     |                 |                 |  |  |  |
| Operating          | Full Load, Max Eout, Case Temp.    | +10°C to +45°C   |                     |                 |                 |  |  |  |
| Storage            | Non-Operating, Case Temp.          | -40°C to +85°C   |                     |                 |                 |  |  |  |
|                    |                                    | Extended temperature operation is available, please contact the factory.             |                     |                 |                 |  |  |  |
| ALTITUDE           |                                    | ALL MODELS   |                     |                 |                 |  |  |  |
| Operating          | Standard Package                   | 0 to 10,000 ft   |                     |                 |                 |  |  |  |
| Storage            | Standard Package                   | 0 to 50,000 ft   |                     |                 |                 |  |  |  |
| HUMIDITY           |                                    | ALL MODELS   |                     |                 |                 |  |  |  |
| Operating          | Standard Package                   | 0 to 95% non-condensing  |                     |                 |                 |  |  |  |
| Storage            | Standard Package                   | 0 to 95% non-condensing  |                     |                 |                 |  |  |  |
| PACKAGING          |                                    | ALL MODELS   |                     |                 |                 |  |  |  |
| Chassis Length     | Not including mounting feet        | 18.5in (469.9mm)   |                     |                 |                 |  |  |  |
| Chassis Width      | Not including mounting feet        | 17.0in (431.8mm)   |                     |                 |                 |  |  |  |
| Chassis Height     | Not including mounting feet        | 5.0in (127.0mm)  |                     |                 |                 |  |  |  |
| Front Panel Length | Not including handles or controls  | 19.0in (482.6mm)   |                     |                 |                 |  |  |  |
| Front Panel Width  | Not including handles or controls  | 0.125in (3.18mm)   |                     |                 |                 |  |  |  |
| Front Panel Height | Not including handles or controls  | 5.25in (3U or 133.35mm)  |                     |                 |                 |  |  |  |
| Weight             | Overall (configuration dependent)  | ~ 30 lbs (11.2kg)  |                     |                 |                 |  |  |  |
| Weight             | Shipping (configuration dependent) | ~ 40 lbs (14.93kg)   |                     |                 |                 |  |  |  |

Specifications subject to change without notice.



Making High Voltage Easier!®

**Higher Service, Higher Performance, Higher Reliability**  
©2011, UltraVolt Inc. All rights reserved.

# HV RACK® CONFIGURABLE SERIES

Rack Mount High Voltage Power System

FIGURE A:

## HV Rack Configurable System Block Diagram

Rev. B 9/30/06





FIGURE B: FRONT PANEL




Making High Voltage Easier!®

1800 Ocean Avenue, Ronkonkoma, NY 11779  
Phone: 1-631-471-4444 Fax: 1-631-471-4696 [www.ultravolt.com](http://www.ultravolt.com)

# HV RACK® CONFIGURABLE SERIES

## Rack Mount High Voltage Power System

FIGURE C: REAR PANEL (EXAMPLE)



#### STANDARD HV CONNECTOR:

- Alden B110YX10 (one per channel)

#### CURRENTLY AVAILABLE OPTIONS:

- USB Interface (USB-HV-RACK)
- Floating/Isolated Channels
- SHV Connectors
- Amp Connectors
- Fischer Connectors
- Alden Connectors
- Caton Connectors
- Parker Medical Connectors
- Removable Mounting Feet
- Mounting Slides



| ORDERING INFORMATION |  |
|----------------------|--|
| TYPE:                | DESCRIPTION:   |
| HV-RACK-1-250        | 19" HV Rack with (1) set of meters & controls with 300 watts of LV power configured for: One channel 250W max total output.          |
| HV-RACK-1-500        | 19" HV Rack with (1) set of meters & controls with 600 watts of LV power configured for: One channel 500W max total output.          |
| HV-RACK-1-750        | 19" HV Rack with (1) set of meters & controls with 900 watts of LV power configured for: One channel 750W max total output.          |
| HV-RACK-1-1000       | 19" HV Rack with (1) set of meters & controls with 1200 watts of LV power configured for: One channel 1000W max total output.        |
| HV-RACK-2-250        | 19" HV Rack with (2) sets of meters & controls with 300 watts of LV power configured for: Two channels 250W max combined output.     |
| HV-RACK-2-500        | 19" HV Rack with (2) sets of meters & controls with 600 watts of LV power configured for: Two channels 500W max combined output.     |
| HV-RACK-2-750        | 19" HV Rack with (2) sets of meters & controls with 900 watts of LV power configured for: Two channels 750W max combined output.     |
| HV-RACK-2-1000       | 19" HV Rack with (2) sets of meters & controls with 1200 watts of LV power configured for: Two channels 1000W max combined output.   |
| HV-RACK-3-250        | 19" HV Rack with (3) sets of meters & controls with 300 watts of LV power configured for: Three channels 250W max combined output.   |
| HV-RACK-3-500        | 19" HV Rack with (3) sets of meters & controls with 600 watts of LV power configured for: Three channels 500W max combined output.   |
| HV-RACK-3-750        | 19" HV Rack with (3) sets of meters & controls with 900 watts of LV power configured for: Three channels 750W max combined output.   |
| HV-RACK-3-1000       | 19" HV Rack with (3) sets of meters & controls with 1200 watts of LV power configured for: Three channels 1000W max combined output. |
| HV-RACK-4-250        | 19" HV Rack with (4) sets of meters & controls with 300 watts of LV power configured for: Four channels 250W max combined output.    |
| HV-RACK-4-500        | 19" HV Rack with (4) sets of meters & controls with 600 watts of LV power configured for: Four channels 500W max combined output.    |
| HV-RACK-4-750        | 19" HV Rack with (4) sets of meters & controls with 900 watts of LV power configured for: Four channels 750W max combined output.    |
| HV-RACK-4-1000       | 19" HV Rack with (4) sets of meters & controls with 1200 watts of LV power configured for: Four channels 1000W max combined output.  |

Note: The sum of the output power capability of the modules cannot exceed the total rack power capability. Please contact the factory to configure your HV Rack part number.

Exceeding 250W in a single channel is possible by paralleling UltraVolt's High Power C Series of 250W models.